

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau




(43) International Publication Date  
4 November 2004 (04.11.2004)

PCT

(10) International Publication Number  
**WO 2004/094852 A1**

- (51) International Patent Classification<sup>7</sup>: **F16D 1/08**, F16C 35/02, 35/073, 35/077
- (21) International Application Number: PCT/GB2004/001681
- (22) International Filing Date: 16 April 2004 (16.04.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
0308957.0 17 April 2003 (17.04.2003) GB
- (71) Applicant (for all designated States except US): **LIL-  
LISHALL PLASTICS AND ENGINEERING LIM-  
ITED** [GB/GB]; Amber Way, Halesowen, West Midlands  
B62 8WG (GB).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **WOODHEAD**,  
Niki, Samuel [GB/GB]; Flat 10, 6 Beaufort Road, Clifton,  
Bristol BS8 1JZ (GB). **SLAYNE**, Andrew, Robert  
[GB/GB]; 8 Brookside Drive, Frampton Cottrell, Bristol  
BS36 2AF (GB).
- (74) Agents: **CALDERBANK**, Roger, T. et al.; Mewburn El-  
lis LLP, York House, 23 Kingsway, London, Greater Lon-  
don WC2B 6HP (GB).
- (81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.
- (84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-  
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,  
GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,  
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,  
ML, MR, NE, SN, TD, TG).
- Published:**  
— with international search report  
— before the expiration of the time limit for amending the  
claims and to be republished in the event of receipt of  
amendments
- For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: TOLERANCE RING ASSEMBLY



(57) Abstract: A tolerance ring has a band (16) with outwardly extending corrugated protrusions forming waves (2) which engage a surface (8) of the bore (4) in a housing (5). At one end of the tolerance ring is an outwardly flared guide surface (15a, 15b) extending axially from the band (16). The guide surface (15a, 15b) acts as an enlarged entrance to the band (16) for a shaft (3) to be mounted in the bore (4) by insertion into the tolerance ring. The use of the guide surface (15a, 15b) assists assembly and reduces or eliminates particle production. It is also possible for the corrugated portions to extend inwardly, for the guide surface to be inwardly flared, and for the tolerance ring to be mounted on the shaft prior to insertion in the bore.